MTouch II Datasheet

Introduction

Designed with the idea of multi-function all-in-one, the MTouch II touch panel allows you to easily perform call control, camera control, content sharing, and other functions. At the same time, MTouch II has a built-in Human Motion Sensor that the conference system can be automatically waken up and you can immediately start the conference.



Specifications

Specifications	Description
MTouch II	 Scratch resistent screen 8-inch IPS screen 1280 x 800 resolution Screen brightness 290 cd/m² Screen contrast 1000:1 10-point capacitive touch screen 3.5mm headset jack Human Motion Sensor Angle adjustable bracket (28° ~ 50°) 1080P/30FPS FHD for sharing Support wired and wireless content sharing Built-in Wi-Fi AP for Yealink wireless presentation device HDMI 2.0 ingest/USB-C video input
Product Diemention (W.D.H)	 MTouch II: 202mm x 151mm x 100mm N.W/CTN: 1kg
Package Features	 Carton Meas: 265 mm x 203 mm x 148 mm N.W/CTN: 0.99Kg G.W/CTN: 1.25Kg

Device Compatibility

- Teams Room Accessories Compatibility Lists
- Zoom Rooms Accessories Compatibility Lists

How to Use

MTouch II has different features when used with different video conferencing endpoints. For more information, please refer to the corresponding documents.

Teams Version:

• Connect the MTouch II to MVC System: MVC System

Zoom Version:

• Connect the MTouch II to ZVC System: ZVC System